

T H E R M A L P O S P R I N T E R S

ODP 200

THE ULTIMATE POS SOLUTIONS

Designed by AURES to complement Odysseé, with which it perfectly links at the point of sale, ODP 200 has rounded and soft curves in stark contrast to the straight lines and sharp angles of traditional POS printers •



The interchangeable cover of the ODP200 is available in the same seven colours as the Odysseé, enabling it to adapt to its environment in the twinkling of an eye, changing from white to orange, from blue to red and yellow.

Fast (150 mm/sec) and reliable, the ODP 200 uses a thermal paper roll with a diameter of max 102mm; it supports various paper/ticket widths (standard 80mm + adaptable from 50 to 82.5 mm); it is equipped with an ESC/POS compatible driver and an easy paper loading system, for quality printing. Its rear paper introduction system also enables the printing of fanfold receipts.

ODP200 is also equipped with 1 cash drawer kick-out port, and operates with serial, parallel, USB, Ethernet and wi-fi interfaces. Superb print quality completes this excellent package.

www.aures.com

*POS|igne is a trademark of AURES Technologies

Fast 150mm/s print

Easy paper drop-in

Thermal roll ø 102 mm max

ESC/POS compatible

**USB, Ethernet, Wi-Fi interface
(option)**

**rear paper introduction system
for fanfold format printing**



Colours of the system base

- pearl
- graphite

Colours of the clips

- tonic orange
- carmine red
- pure white
- spice yellow
- soft blue
- indigo blue
- metal grey



ODYSSEÉ with ODP 200

MODEL

ODP 200

Printing method	Direct Thermal
Printing speed	150mm/sec
Effective printing width	72 mm : 512 in 180 DPI / 576 in 203 DPI
Resolution	180 DPI or 203 DPI
Paper loading	«easy paper drop-in» system

CHARACTER/LINE

Font A	42 columns 180 DPI / 48 columns 203 DPI
Font B	56 columns 180 DPI / 64 columns 203 DPI

PAPER TYPE

THERMAL PAPER

Width	80 mm standard - from 50 up to 82.5 mm
Thickness	0.065 ~ 0.1mm
Roll diameter	76 mm standard - max. 102 mm

CHARACTER SET

Alphanumeric characters	95
Extended graphic	128 / 7 Page(1 space page)
International caracters	10
Barcode	EAN-8, EAN-13, CODE 39, CODE 93, CODE 128, ITF UPC-A, UPC-E, CODABAR, PDF 417
Emulation	ESC/POS* command compatible
Sensor	Paper end sensor
Draw port	1 ports
Interface	Serial(RS-232C), Parallel(IEEE-1284), USB combo, Ethernet Interface(10Mbps), Wi-Fi(802,11b)
Power	external 24 V - 2.5A - 110 x 65 x 30 mm

AUTO CUTTER

Type	Guillotine
Life	1,000,000 cuts
Cutting method	Full/Partial Cut

Dimension (W/D/H)	152 x 222.3 x 156.2 mm
Weight	1.7 Kg

*ESC/POS is a trade mark of Seiko Epson Corporation.